

## Nonprovisional Utility Patent Reissue Application

Title of Invention: LAUNDRY ROLL HAMPER

Patent No.: US 6,481,591 B2

Date of Patent: Nov. 19, 2002

Inventors: Rey Zabat Mendoza, Wilhelmina Navarro Mendoza

Amend ABSTRACT as follows:

A cylindrical hamper bag or covering snugly fit over an internal frame that includes a circular top, a circular base, and at least six vertically upstanding leg members. The six leg members are of equal height and include hinges at the points connecting the leg members to the top and the base, and at at least two equidistant points [a third and two thirds] of the length of each leg member permitting pivotal movement. The pivotal movement of the leg members allow the hamper to expand outwards and change shape from a cylindrical to a polygon shape ball or sphere.

Amend the paragraph beginning at column 1, line 20, as follows:

This invention relates to a hamper for storing and transporting clothes, specifically to such laundry hampers, bags, and baskets which are used for carrying or transporting soiled clothes from one location (e.g., upstairs bathroom) to another location in the house (e.g., the laundry room in the basement) or, in the case of a dormitory or apartment building, to the laundry room located on one end of the building or on a different floor. [other laundry establishment.] More particularly, this invention relates to an improved laundry hamper with features which allows the hamper assembly to expand and resemble a polygon-shaped ball or have a spherical shape.

Amend the paragraph beginning at column 1, line 29, as follows:

Hampers in general, and laundry hampers in particular, are available in a great variety of types and designs. One type of hamper comprises a container, often constructed of wicker or plastic that forms a storage chamber for soiled clothing. Such hampers ordinarily have a top closure or cover that is attached to the container and serves to shut the container when it is not in use. This type of hamper is either too heavy or bulky to carry. Soiled clothing that have accumulated within the hamper must periodically be transferred to a basket or other transport means, which is then carried to the washing machine which is in another location of the house or building. An example of a clothes hamper of this type is illustrated in U.S. Pat. No. D412,229. A similar type hamper includes a handle and wheels to facilitate transport to the laundry room. However, this type still needs to be held or carried down the stairs. An example of a hamper of this type is illustrated in U.S. Pat. No. D413,099.

Amend paragraph beginning at column 1, line 64, as follows:

It is an object of the present invention to provide a lightweight and expandable hamper assembly that can be reshaped from a cylindrical to a polygon-shaped ball or spherical shape (depending on the number of leg hinges used) in order to solve a previously unrecognized problem of having to carry the full hamper or having to transfer the soiled clothing to a laundry basket or bag for transporting to the laundry room in another part of the house or building.

Amend paragraph beginning at column 2, line 26, as follows:

In one preferred embodiment, a hamper bag or covering is supported on an upright position by an internal frame having a top, a base, and at least six vertically upstanding leg members. In this

embodiment, the leg members are joined to the top and the base at equal distances and parallel to one to the other at right angles. The leg members are joined to the top and the base by hinges. Each leg member also contains hinges at at least two equidistant points [one third and two thirds] of the length of each leg. The hamper bag or covering encloses the entire frame and is folded over the top of the circular top frame to create an opening and is held in place by a securing means such as Velcro. A top cover is hinged to the top frame and is secured shut by Velcro. The hamper expands outwards in the middle section and changes its shape from a cylindrical to a polygon-shaped ball or spherical shape (depending on the number of leg hinges used), which can then be rolled.

Amend the paragraph beginning at column 2, line 41, as follows:

Laundry hampers are commonly used and placed in bathrooms in the upper floors of the house where most bedrooms are located. When it comes time to doing the laundry, the hampers are either carried or the soiled clothes are transferred from the laundry hampers to laundry baskets, which are hand-carried down the stairs, across the living room, dining room, kitchen, or family room to the laundry room located on the first floor or down the basement. In the case of dormitories and apartment buildings, they have to be carried down the hallways or to a different floor to the laundry room. Carrying the load and navigating from the upstairs bathroom, down the stairs, to the laundry room is both physically challenging and risky. Existing laundry bags, hampers, and baskets do not address or resolve this issue.

Amend the paragraph beginning at column 2, line 53, as follows:

It is the object of the present invention to:

- (a) Provide a laundry hamper which does not have to be carried from the upstairs bathrooms, down the stairs, across various rooms, hallways, to the laundry room on the first floor, or down the basement, or to the end of the building;
- (b) Provide a laundry hamper that does not have to be emptied and the clothes transferred to a laundry bag or basket for transporting to a laundry room;
- (c) Provide a cylindrical laundry hamper that expands and changes shape to resemble a [hexagon or] polygon-shaped ball or sphere so that it can be rolled with minimal effort instead of carried;

Further objects and advantages are to provide a laundry hamper that is lightweight, simple and economical to manufacture, allows airflow, and can be handled by persons of almost any age.

Amend the paragraph beginning at column 3, line 3, as follows:

A preferred embodiment of the laundry roll hamper is illustrated in FIG. 1 (upright position) and FIG. 2 (expanded position). The laundry roll hamper is composed of a fabric or woven nylon bag or covering **10** and an internal frame made of plastic or other flexible, lightweight material. Bag or covering **10** encloses the entire frame and folds over a circular top frame **14** creating an opening and is secured by Velcro. A top cover **12** of plastic or other lightweight material or fabric similar to bag or covering **10** serves as the top closure. Top cover **12** is attached to top frame **14** by a cover hinge **16** creating a flap for opening and closing. Velcro secures top cover **12** when the top is closed and secured. Top frame **14** is joined to six or more vertical leg members **18** by frame hinges **20**, which allow leg members **18** to be repeatedly bent outwards and straightened without fracturing. Frame hinges **20** are of the type that only allow leg members **18** to bend outwards but not inwards when straightened. Each of leg members **18**,

in turn, have at least two leg hinges **22** that are equidistant to frame hinges **20** at the top, to each other, and to frame hinges **20** at the bottom. Leg hinges **22** are the pivot points that allow [the top third and the bottom third of] leg members **18** to bend outward at [45-degree angles] the equidistant points resulting in a polygon-shaped ball or spherical shape (depending on the number of leg hinges **22** used) [while the middle third remains in a vertical orientation]. Leg hinges **22** are of the type that causes leg members **18** to snap and lock in place at or close to the vertical (90-degrees) and at the bent [(45-degrees)] positions. Leg hinges **22** will not allow leg members **18** to bend inwards beyond the vertical when straightened. Bag or covering **10** secures the middle portion of leg members **18** by Velcro or other fastening means in order to maintain each of leg members **18** positions and equal distance to one another. The bottom of leg members **18** are joined to a circular base frame **24** by frame hinges **20**. Base frame **24** is made of the same material as top frame **14** and leg members **18**. Base frame **24** has the same diameter as top frame **14** and is wide enough to allow the entire structure to stand upright when the hamper is empty and remain stable when the hamper is full and expanded. Bag or covering **10** also encloses the base. The laundry roll hamper can be made of various sizes, colors, designs, and combinations of fabric and material to fit ones needs and desires.

Amend the paragraph beginning at column 3, line 44, as follows:

The empty laundry roll hamper is upright as shown in FIG. 1. Soiled clothes are deposited by opening the top cover **12** and dropping the clothes through the opening at top frame **14**. The hamper maintains its shape and position as it is filled with clothes. When the hamper is full, or even partially full, downward pressure is exerted on top frame **14**, or outward pressure to leg hinges **22** at each of leg members **18**, which then bend outwards at the pivot points at frame

hinges **20** and leg hinges **22** causing the hamper to expand and resemble a [hexagon or] polygon-shaped ball or sphere, as shown in FIG. 2. Leg members **18** are locked in the bent position.

Base frame **24** keeps the expanded hamper stable until it is ready to be moved. Top cover **12** is then secured to top frame **14** by Velcro to prevent the clothes from falling off when the hamper is finally rolled. Pushing with either the hands or the feet, whichever is preferred, allows the expanded laundry hamper to roll with minimal effort. The [hexagon or] polygon or spherical shape provides some degree of control over flat surfaces and, if need be, can be controlled down the stairs with the hand. Otherwise, the laundry roll hamper can simply be allowed to roll down the stairs. The lightweight material used for the frame and covering should not cause any damage to stair railings, walls, or floors that it may come in contact with as it rolls down. The entire frame of the laundry roll hamper remains flexible and pliant yet maintains its shape as it is rolled from the upstairs bathroom, through the passageway, down the stairs, through the living room, kitchen, or family room, to the laundry room on the first floor or further down the hallway or [the] basement. In the laundry room, top cover **12** is then unfastened and opened to remove the clothes. After the clothes are removed, leg members **18** can then be straightened by pulling up on top frame **14** while holding down base frame **24** with the feet. Or, by manually applying simultaneous inward pressure to opposite leg hinges **22** to unlock and bring the laundry roll hamper back to the upright position where the leg members again lock in place.

Amend the paragraph beginning at column 4, line 33, as follows:

While the above description contains many specifications, these should not be construed as limitations of the scope of the invention, but rather as an exemplification of one preferred embodiment thereof. Many other variations are possible. For example, the bag or covering and

top cover can be of various material, fabrics, color, designs, prints, etc.; the top cover can be secured by Velcro, zipper, or other means. The entire frame can be made of plastic or other lightweight, pliant material, or combination thereof, and vary in size and shape. The vertical leg members can each have more than two leg hinges, the numbers of which will determine the degree of spherical shape it has in the expanded state. The hamper itself can be made of various sizes to fit ones needs and desires.

Claim 1. (amended)

What we claim as our invention is:

- A partially collapsible hamper having a cylindrical upright state and a polygon-shaped ball or spherical expanded state, comprising a top and bottom circular frame, a plurality of pivoting vertical leg members extending between the top and bottom circular frames, a body of flexible sheet material extending from the top circular frame down to and enclosing the vertical legs and bottom circular frame, said vertical leg members are connected to the top and bottom circular frames by hinges, each vertical leg member divided into at least three equal length parts and joined together by at least two hinges at equidistant points [a third and two thirds] of the length of each leg member, the improvement comprising said hinges that lock said leg members in the vertical position until downward pressure is applied to unlock the hinges and cause movement of [move the top third and bottom third portions of] said leg members to bend outward and away from the center [to 45-degree angles from the vertical] forming a polygon-shaped ball or spherical shape (depending on the number of leg hinges used) where said hinges again lock in place. [while the middle third portion of said leg members remain in the upright vertical orientation].